



McGuire Manufacturing Co., Inc.

60 Grandview Court
 P.O. Box 746 ♣Cheshire, CT 06410
 203-699-1801 ♣ Fax: 203-699-1813
 www.mcguiremfg.com

Part No.


**8872, 8902, 8902CNC,
 8912, 8912CNC, 8903, 8904**

**Cast Body P-Trap
 With or Without Cleanout**

PRODUCT SPECIFICATION

Job Name:

Submittal Number:



PROFESSIONAL LINE

ROUGHING MEASUREMENTS

NO.	TRAP DIMENSIONS		A	B	C to E
	INLET	OUTLET			
8872	1-1/4"	1-1/4"	5"	4-1/2"	11"
8902	1-1/4"	1-1/2"	5"	4-1/2"	12"
8902CNC	1-1/4"	1-1/2"	4-5/8"	4-1/8"	12"
8912	1-1/2"	1-1/2"	5"	4-1/2"	12"
8912CNC	1-1/2"	1-1/2"	4-5/8"	4-1/8"	12"
8903	1-1/2"	2"	5"	6"	13"
8904	2"	2"	5"	6"	13"

**FED SPEC W.W.P. 541
 CAST BRASS P TRAP
 MINIMUM SEAL 2"**



See options and accessories section for details on product variations.

Specifications:

P-Trap shall be chrome plated cast brass body (with, without) cleanout, with 17 gauge seamless tubular wall bend, cast brass slip nuts. Reducing washers shall be used with reducing cast brass nut. With (shallow, deep, bell) (steel, brass) or (forged brass with set screw) flange. P-Trap shall be McGuire "Classic" Professional Line (8872C, 8902C, 8912C, 8903, 8904). Trap shall be certified by CSA or other recognized testing authority. P-Trap shall bear manufacturer and testing mark.