

LITE COMMERCIAL ADJUSTABLE 17 GAUGE TUBULAR P-TRAPS

Roughing Measurements							
Model No.	INLET	OUTLET	A	в	C to E	Flange	Slip Nut
MCT125085	1-1/4"	1-1/4"	5"	4-1/2"	11-1/2"	Shallow	Brass
MCT125085B	1-1/4"	1-1/4"	5-1/4"	4-1/2"	11-1/2"	Box	Brass
MCT125085NC	1-1/4"	1-1/4"	5"	5"	11-1/2"	Shallow	Brass
MCT125085NCB	1-1/4"	1-1/4"	5"	4-5/8"	11-1/2"	Box	Brass
MCT125075ZN	1-1/4"	1-1/4"	5-1/4"	4-3/4"	10-1/2"	Shallow	Zinc
MCT125075NCZN	1-1/4"	1-1/4"	5"	4-1/2"	10-1/2"	Shallow	Zinc

- Rated Operating Temperature: 40-140°F
- Note: 180°F max. during temporary high-temperature system flush

Suffix Designations NC = No Cleanout Plug

GJ = Ground Joint Wall Bend

Specifications:

P-Trap shall be 17 gauge seamless chrome plated tubular brass with wall bend and flange.





This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

© 2022 McGuire Manufacturing Co., Inc. All rights reserved / I Traps / www.mcguiremfg.com